



Specifications Ledvance LED  
Downlight Alu DN200 25W 2250lm  
100D - 830 Warm White | 215mm -  
IP44

[View Product](#)

General Information

|                          |                                     |
|--------------------------|-------------------------------------|
| SKU                      | 233339                              |
| EAN                      | 4058075091498                       |
| Brand                    | Ledvance                            |
| Manufacturer Name        | DL ALU DN200 25W/3000K WT IP44 LEDV |
| Any Lamp all-in warranty | 5 Years                             |
| Average Lifetime (h)     | 50000                               |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x26               |
| Wattage                     | 25.000000          |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Not Dimmable       |
| Colour temperature (Kelvin) | 3000K - Warm White |
| Colour Code                 | 830 Warm White     |
| Colour Rendering (Ra)       | 80-89              |
| Driver Included             | Yes                |
| Beam Angle (degree)         | 100                |

|                          |                                       |
|--------------------------|---------------------------------------|
| Luminous Flux (Lumen)    | 2250                                  |
| Luminous Efficacy (lm/W) | 90                                    |
| Power factor             | >0.90                                 |
| Installation Depth (mm)  | 120                                   |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PMMA (Polymethyl methacrylate)        |
| Suitable for Outdoor     | No                                    |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-rating              | IP44                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +45                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Series                 | DOWNLIGHT ALU                 |

## Dimensions

Height (mm)

**Why Any-lamp?**

61

Diameter (mm)

215



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

Type of sensor

No Sensor

