## Specifications Philips LED Panel Coreline RC132V 33W 3600lm - 840 Cool White | 60x60cm - UGR <19 - Emergency 3H

[View Product](#)

## Product Details

| | |
|---|---|
| Series | RC132V |

## General Information

| | |
|---|---|
| SKU | 238221 |
| EAN | 8718699967116 |
| Brand | Philips |
| Manufacturer Name | RC132V G4 LED36S/840 PSU W60L60 OC ELB3 |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |

## Technical Information

| | |
|---|---|
| Technology | LED Integrated |
| Replaces (Watt) | 4x18 |
| Wattage | 33.000000 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour temperature (Kelvin) | 4000K - Cool White |
| Colour Code | 840 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Beam Angle (degree) | 90 |

| | |
|---|---|
| Luminous Flux (Lumen) | 3600 |
| Luminous Efficacy (lm/W) | 123 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Fixture Connection | Push-in-connector, 4-pole |
| Driver Included | Yes |
| Power factor | >0.90 |
| Product Type Category | LED Panel |
| Type of sensor | No Sensor |

## Fixture Information

| | |
|---|---|
| Mounting Method | Recessed |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PS (Polystyrene) |
| Operating Temperature | -10 to +40 |
| Emergency Lighting | 3H Emergency Light |
| Colour of the Fixture | White |
| Housing | Steel |
| Colour of material | White |

## Dimensions

| | |
|---|---|
| LED panel size | 60x60cm |
| Length (mm) | 595 |
| Width (mm) | 595 |
| Height (mm) | 16 |

Up to **7 years warranty**     **Easy** return process