



Specifications Philips LED Downlight
 LuxSpace Compact Low Height
 DN570C VLC-E 16.5W 2200lm 80D - 830
 Warm White | 250mm - Aluminium
 Reflector - Dali Dimmable

[View Product](#)

General Information

| | |
|--------------------------|----------------------------------|
| SKU | 238728 |
| EAN | 8718699970925 |
| Brand | Philips |
| Manufacturer Name | DN570C LED20S/830 PSD-VLC-E C WH |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 70000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |
| Beam Angle (degree) | 80 |

| | |
|--------------------------|--------------------------|
| Luminous Efficacy (lm/W) | 133 |
| Power factor | >0.90 |
| Unified Glare Rating | < 22 - for general areas |
| Optical Cover | PC (Polycarbonate) |
| Finish of Reflector | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|---|
| EOC8 | 97092500 |
| Mounting Method | Surface |
| Cut out (mm) | 223 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | +10 to +25 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | PIP [Push-in connector and pull relief] |
| Series | DN570C |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 96 |
| Diameter (mm) | 250 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



Easy return process