



Specifications Noxion LED Panel Delta Pro V2.0 Highlum 40W 5480lm - 840 Cool White | 120x30cm - UGR <19 - Philips Xitanium Driver - Emergency 1H

[View Product](#)

General Information

|                          |                                                                                             |
|--------------------------|---------------------------------------------------------------------------------------------|
| SKU                      | 243438                                                                                      |
| EAN                      | 8719157035620                                                                               |
| Brand                    | Noxion                                                                                      |
| Manufacturer Name        | NEW Noxion LED Panel Delta Pro UGR<19 Highlum V2.0 40W 5480lm 4000K 300x1200+Noodintegratie |
| Any Lamp all-in warranty | 6 Years                                                                                     |
| Average Lifetime (h)     | 70000                                                                                       |
| Series                   | Delta Pro                                                                                   |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x36            |
| Wattage                     | 40              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |

|                          |                        |
|--------------------------|------------------------|
| Luminous Flux (Lumen)    | 5480                   |
| Luminous Efficacy (lm/W) | 120                    |
| IP-rating                | IP20                   |
| Impact Protection (IK)   | IK02 - 0.20 joule      |
| Fixture Connection       | PI [Push-in connector] |
| Power factor             | >0.90                  |
| Product Type Category    | LED Panel              |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | 1H Emergency Light             |
| Colour of the Fixture | White                          |
| Housing               | PS (Polystyrene)               |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 32       |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process