



Specifications Noxion LED Trunking NX-Line V2 70W  
12600lm 120D - 840 Cool White | 1500mm - Dali  
Dimmable - 8-Pole - UGR <24

[View Product](#)

## General Information

|                          |                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------|
| SKU                      | 248169                                                                                   |
| EAN                      | 8719157046022                                                                            |
| Brand                    | Noxion                                                                                   |
| Manufacturer Name        | Noxion LED Linear Light NX-Line V2.0 Module 1500mm 70W 4000K FD120 WH DALI (PC Diffuser) |
| Any Lamp all-in warranty | 6 Years                                                                                  |
| Average Lifetime (h)     | 50000                                                                                    |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Wattage                     | 70                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour of Light             | White              |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 12600              |
| Luminous Efficacy (lm/W)    | 180                |
| Beam Angle (degree)         | 120                |

|                       |              |
|-----------------------|--------------|
| Power factor          | >0.90        |
| Including bulb        | Yes          |
| Product Type Category | LED Trunking |

## Fixture Information

|                        |                                |
|------------------------|--------------------------------|
| Mounting Method        | Suspended                      |
| Fixture Connection     | Plug-in 230V                   |
| Optical Cover          | PMMA (Polymethyl methacrylate) |
| IP-rating              | IP20                           |
| Impact Protection (IK) | IK04 - 0.50 joule              |
| Operating Temperature  | -20 to +60                     |
| Housing                | PC (Polycarbonate), Steel      |
| Colour of the Fixture  | White                          |
| Colour of material     | White                          |
| Emergency Lighting     | No Emergency Unit              |
| Series                 | NX-Line                        |

## Dimensions

|             |      |
|-------------|------|
| Length (mm) | 1499 |
| Width (mm)  | 69.5 |
| Height (mm) | 39.4 |

## Sensor Information

## Why Any-lamp?

|                                                                                                                                                                                                                                                                   |           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Type of sensor                                                                                                                                                                                                                                                    | No Sensor |
|  Order from the <b>largest lighting specialist</b> in Europe  <b>Customised</b> quotation |           |
|  Up to <b>7 years warranty</b>  <b>Easy</b> return process                                  |           |