



Specifications Noxion LED Panel Delta Pro V4 Aluminium/Metal White 29W 3700lm - 830 Warm White | 60x60cm - Dali Dimmable - UGR <22

[View Product](#)

General Information

|                          |                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------|
| SKU                      | 248846                                                                                  |
| EAN                      | 8719157048378                                                                           |
| Brand                    | Noxion                                                                                  |
| Manufacturer Name        | Noxion LED Panel Delta Pro V4 29W 3700lm 3000K 600*600 UGR<22 (4x18W eqv.) DALI dimbaar |
| Any Lamp all-in warranty | 6 Years                                                                                 |
| Average Lifetime (h)     | 50000                                                                                   |
| Series                   | Delta Pro                                                                               |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 29                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 3700               |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 128               |
| IP-rating                | IP40/IP20         |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Fixture Connection       | Fast connector    |
| Finish of Reflector      | PET               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                          |
|-----------------------|--------------------------|
| Mounting Method       | Recessed                 |
| Unified Glare Rating  | < 22 - for general areas |
| Optical Cover         | PS (Polystyrene)         |
| Operating Temperature | -20 to +40               |
| Emergency Lighting    | No Emergency Unit        |
| Colour of the Fixture | White                    |
| Housing               | Aluminium, Metal         |
| Colour of material    | White                    |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 14      |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process