



Specifications Multipack 6x Ledvance  
LED Waterproof Batten Damp Proof  
Value 50W 6000lm - 840 Cool White |  
150cm



[View Product](#)

General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 253275                                  |
| EAN                      | 8719157060721                           |
| Brand                    | Ledvance                                |
| Manufacturer Name        | Multipack 6x DP VAL 1500 50W/4000K IP65 |
| Any Lamp all-in warranty | 3 Years                                 |
| Average Lifetime (h)     | 50000                                   |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x58            |
| Wattage                     | 50              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour of Light             | White           |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 70-79           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 6000            |
| Luminous Efficacy (lm/W)    | 120             |

|              |       |
|--------------|-------|
| Power factor | >0.90 |
|--------------|-------|

|                |     |
|----------------|-----|
| Including bulb | Yes |
|----------------|-----|

|        |       |
|--------|-------|
| Length | 150cm |
|--------|-------|

|                       |                       |
|-----------------------|-----------------------|
| Product Type Category | LED Waterproof Batten |
|-----------------------|-----------------------|

## Fixture Information

|                 |         |
|-----------------|---------|
| Mounting Method | Surface |
|-----------------|---------|

|                    |                    |
|--------------------|--------------------|
| Fixture Connection | Screwless terminal |
|--------------------|--------------------|

|               |                    |
|---------------|--------------------|
| Optical Cover | PC (Polycarbonate) |
|---------------|--------------------|

|           |      |
|-----------|------|
| IP-rating | IP65 |
|-----------|------|

|                        |                 |
|------------------------|-----------------|
| Impact Protection (IK) | IK08 - 5 joules |
|------------------------|-----------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | -20 to +40 |
|-----------------------|------------|

|                       |      |
|-----------------------|------|
| Colour of the Fixture | Grey |
|-----------------------|------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|        |       |
|--------|-------|
| Series | Value |
|--------|-------|

## Dimensions

|             |      |
|-------------|------|
| Length (mm) | 1500 |
|-------------|------|

|            |    |
|------------|----|
| Width (mm) | 77 |
|------------|----|

|             |    |
|-------------|----|
| Height (mm) | 68 |
|-------------|----|

## Sensor Information

|                |
|----------------|
| Type of sensor |
|----------------|

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

